

# POLYSTRAP MACHINES



## ALLPACK

### FEATURES

- Light compact design
- Easy operation, simple maintenance
- Hinged stainless steel tabletop
- Adjustable table height : 30" - 36"
- Rigid casters with brake
- Automatic timed motor stop
- Reliable P.C. board electrical control

### SPECIFICATIONS

**Power** 120 Volts,  
**Supply:** Single Phase Strap  
**Tension:** Variable from 10 to 99 lbs.  
**Strap** 1/4", 3/8", 1/2"  
**Width:** 6 mm, 9 mm, 12 mm  
 8" x 8" or 9" x 8" ID Core

**Strap**  
**Type:** STRAPEX type "HG" or "AMS"  
**Package** Min. 4" W x 2" H  
**Sizes :** Max: Unlimited

**Machine**  
**Dim.:** 34" L x 22" W x 30" H  
**Weight:** 185 lbs.



## BETA 100

**Auto Strap Feeding**  
 Simply insert the strap into the feed rollers and push the rest button.

### Electronic

#### Tension Control

External tension adjustment on the control panel.

#### Auto Strap Ejection

Loop-eject clears unwanted strap automatically if the machine is cycled without a package.

#### Strap End Ejector

End of strap sensor ejects end of coil out and prepares for next coil of strap.

### FEATURES

- Durable, reliable
- Easy operation, simple maintenance
- Easy and fast strap loading
- Rigid casters
- Roller top
- Footswitch and photo eye operation

### SPECIFICATIONS

#### Production

**Speed:** up to 29 straps per minute

#### Strap

**Width:** 3/8" or 1/2"  
 9 mm or 12mm

#### STANDARD ARCH SIZES

25" W x 16" H	33" W x 16" H
25" W x 24" H	33" W x 24" H



## OMEGA

**Compact Mechanical Head**  
 With 30% fewer parts than comparable machines the Omega requires fewer adjustments, has fewer wear components and requires less maintenance.

#### Auto Strap Feeding

Simply insert the strap into the feed rollers and push the start button.

#### Electronic Tension Control

External tension adjustment on the control panel.

#### Auto Strap Ejection

Loop-eject clears unwanted strap automatically if the machine is cycled without a package.

#### Strap End Ejector

End of strap sensor ejects end of coil out and prepares for next coil of strap.

### SPECIFICATIONS

#### Production

**Speed:** up to 50 straps per minute

#### Strap

**Width:** 3/16", 1/4", 3/8"  
 5 mm, 6 mm, 9 mm  
 8" x 8" ID Core

#### STANDARD ARCH SIZES

22" W x 16" H
25" W x 20" H



## Signode LBX-2000

### Plastic strapping machine

Signode's new LBX-2000™ offers the most reliable performance, lowest maintenance cost and highest speed of any general duty strapping machine on the market today

- Up to 70 straps per minute
- Jam-resistant technology
- Automatic refeed
- Lubrification-free
- No internal adjustments necessary

**Cycle rate:** Up to 70 straps per minute

#### Chute inner dimensions:

	Small chute		Large chute	
	Inches	mm	Inches	mm
A	20	510	28	710
B	15	380	15	380

**Call about fully automatic and custom machines**

**We service all machines that we sell... as well as other makes and models**